

APPENDIX A OF TYPE EXAMINATION CERTIFICATE

Product Characteristics

TX Frequency:	VHF: 144-146 MHz; UHF: 430-440 MHz
RX Frequency:	VHF: 144-146 MHz; UHF: 430-440 MHz
ITU Designation:	F3E
Output Power:	VHF (Conducted): 5 Watts (High), 2 Watts (Middle), 1 Watt (Low) UHF (Conducted): 4 Watts (High), 2 Watts (Middle), 1 Watt (Low)
Modulation:	FM
Antenna:	Whip Antenna, 2 dBi

Conformity Details

Requirement	Standard, Test Report Number, Date & Laboratory
Radio Spectrum	EN 301 783 V2.1.1 (2016-01) Test Report RXM161028057-22 issued on 2017-02-21 by BACL, Dongguan
EMC	EN 301 489-1 V1.9.2 (2011-09), ETSI EN 301 489-15 V1.2.1 (2002-08) Test Report RXM161028057-02 issued on 2017-02-21 by BACL, Dongguan
Safety	EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011 + A2: 2013 Test Report R2XM161028057-03 issued on 2016-11-17 by BACL, Dongguan
Health	EN62311: 2008 Test Report RXM161028057-20 issued on 2017-02-22 by BACL, Shenzhen

***** End of Appendix *****

